## **Claims**

What is claimed is:

1. A method of generating data traffic in a traffic generator, the method comprising the steps of:

5

generating a plurality of traffic flows; and

associating each of the traffic flows with at least one of a plurality of output interfaces of the traffic generator such that each of at least a subset of the plurality of output interfaces has two or more of the traffic flows associated therewith.

10

- 2. The method of claim 1 wherein at least one of the traffic flows is generated based on user selection of at least one of a protocol encapsulation, a packet size distribution model, a packet arrival time distribution model, a traffic model, and a packet payload description.
- 3. The method of claim 1 wherein the output interfaces are associated with an output interface bus of the traffic generator.
  - 4. The method of claim 3 wherein the output interface bus is implemented as a software module representative of one or more physical connections.

20

25

- 5. The method of claim 1 wherein each of the plurality of traffic flows maps to one of the output interfaces of the traffic generator and to an input interface of the traffic generator.
- 6. The method of claim 1 wherein the traffic generator is operable in at least two phases, including a first phase in which a timestamp table is constructed based at least in part on user-selected configuration information, and a second phase in which packets are generated using the timestamp table constructed in the first phase.

- 7. The method of claim 1 wherein the traffic generator comprises a pattern generator having a plurality of user-selectable pattern generation processes associated therewith, each of the processes adaptable for generating a configuration list.
- 8. The method of claim 1 wherein the traffic generator comprises a sequencer having a plurality of user-selectable sequencing processes associated therewith, a given one of the sequencing processes specifying an order of selection of items from a configuration list.
- 9. The method of claim 1 wherein the plurality of sequencing processes comprises a group sequencer which provides a correlative mapping between two or more configuration lists and their associated parameters.
  - 10. The method of claim 1 wherein information characterizing one or more of the traffic flows is stored as a traffic file in a memory associated with the traffic generator.
  - 11. The method of claim 10 wherein the traffic file is represented as a string which includes a global header followed by one or more frames each having an associated frame header.

15

25

- 12. The method of claim 11 wherein the global header comprises a type field indicating a
  type of traffic description used, and a clock speed field indicating a clock speed of an associated output interface.
  - 13. The method of claim 11 wherein a given one of the frame headers comprises a flow identification field which identifies one or more traffic flows associated with the corresponding frame, a timing field indicating a time gap in clock cycles between the corresponding frame and a previous frame, and a length field indicating the length of the corresponding frame.

- 14. The method of claim 1 wherein the traffic generator comprises a hardware traffic generator.
- 15. The method of claim 1 wherein the traffic generator comprises a software traffic5 generator.
  - 16. The method of claim 1 wherein the software traffic generator comprises an element of a software-based development tool for simulating the operation of an electronic system.
  - 17. The method of claim 1 wherein the traffic generator is implemented primarily in software and is configured to generate data traffic files that are utilizable in another traffic generator implemented primarily in hardware.
  - 18. An apparatus for generating data traffic, the apparatus comprising an information processing device having a processor and a memory, the information processing device implementing a traffic generator operative:

to generate a plurality of traffic flows; and

10

15

20

25

to associate each of the traffic flows with at least one of a plurality of output interfaces of the traffic generator such that each of at least a subset of the plurality of output interfaces has two or more of the traffic flows associated therewith.

19. An article of manufacture comprising a storage medium containing one or more software programs for use in generating data traffic in a traffic generator, wherein the one or more software programs when executed implement the steps of:

generating a plurality of traffic flows; and

associating each of the traffic flows with at least one of a plurality of output interfaces of the traffic generator such that each of at least a subset of the plurality of output interfaces has two or more of the traffic flows associated therewith.